

36517

```
#ifndef _ENV_H
#define _ENV_H

#include <stdint.h>

// Definir níveis de log
#define LOG_LEVEL_NONE 0 // Sem logs
#define LOG_LEVEL_ERROR 1 // Apenas erros
#define LOG_LEVEL_WARN 2 // Avisos e erros
#define LOG_LEVEL_INFO 3 // Informações, avisos e erros
#define LOG_LEVEL_DEBUG 4 // Mensagens de debug, informações, avisos e erros

// Definir qual o nível de log ativo
#define CURRENT_LOG_LEVEL LOG_LEVEL_ERROR

// Funções de log condicional com base no nível
#define LOG_LEVEL_ERROR 1
#define LOG_LEVEL_WARN 2
#define LOG_LEVEL_INFO 3
#define LOG_LEVEL_DEBUG 4

// Defina o nível de log atual
#define CURRENT_LOG_LEVEL LOG_LEVEL_DEBUG

// Macros de log condicional com suporte para mensagens simples e formatadas
#if CURRENT_LOG_LEVEL >= LOG_LEVEL_ERROR
#define LOG_ERROR(fmt, ...) \
    do \
    { \
        Serial.printf("[ERROR] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_ERROR(fmt, ...)
#endif
```

```

#if CURRENT_LOG_LEVEL >= LOG_LEVEL_WARN
#define LOG_WARN(fmt, ...) \
    do \
    { \
        Serial.printf("[WARN] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_WARN(fmt, ...)
#endif

#if CURRENT_LOG_LEVEL >= LOG_LEVEL_INFO
#define LOG_INFO(fmt, ...) \
    do \
    { \
        Serial.printf("[INFO] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_INFO(fmt, ...)
#endif

#if CURRENT_LOG_LEVEL >= LOG_LEVEL_DEBUG
#define LOG_DEBUG(fmt, ...) \
    do \
    { \
        Serial.printf("[DEBUG] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_DEBUG(fmt, ...)
#endif

// WiFi Network Credentials
constexpr char NETWORK_CLIENT[] = "SmartVac Telemetry";
constexpr char PASSW[] = "br@skem#2023";

constexpr uint32_t DELAY_MS_READER_TASK = 300; //300ms para que os envios sejam feitos a cada
20s

// Define o atraso em milissegundos para tarefas de leitura (10.000 parece ser um número

```

mágico)

```
// Equipment Identifiers
```

```
namespace Equipment
```

```
{
```

```
    constexpr char TAG[] = "36517";
```

```
    constexpr char TOPIC[] = "v4/matr0543";
```

```
    constexpr char SENDING_SERVER[] = "web.smartvac.app";
```

```
    constexpr uint16_t SENDING_PORT = 1883;
```

```
    constexpr unsigned long SENDING_VELOCITY = 115200;
```

```
    constexpr uint16_t SENDING_KEEPALIVE = 200;
```

```
    constexpr uint32_t DELAY_MS = 500; // Delay time in milliseconds for tasks
```

```
}
```

```
// Voltage Calibration Constants
```

```
struct VoltageCalibration
```

```
{
```

```
    static constexpr float CAL_R = 206;
```

```
    static constexpr float CAL_S = 0000;
```

```
    static constexpr float CAL_TT = 000;
```

```
};
```

```
// Current Calibration Constants
```

```
struct CurrentCalibration
```

```
{
```

```
    static constexpr int CAL_R = 15.6;
```

```
    static constexpr int CAL_S = 000;
```

```
    static constexpr int CAL_TT = 000;
```

```
};
```

```
// Pin Definitions
```

```
struct Pins
```

```
{
```

```
    static constexpr int CURRENT_R = 34;
```

```
    static constexpr int CURRENT_S = 33;
```

```
    static constexpr int CURRENT_TT = 36;
```

```
    static constexpr int TEMPERATURE = 16;
```

```
    static constexpr int VOLTAGE_R = 35;
```

```
    static constexpr int VOLTAGE_S = 32;
```

```
    static constexpr int VOLTAGE_TT = 39;
```

```
};
```

```

// Sensor Addresses
namespace Sensors
{
    constexpr char INS[ ] = "s91420";
    constexpr char RET[ ] = "s91421";
    constexpr char SUC[ ] = "s91422";
    constexpr char LL[ ] = "s91423";
    constexpr char ENT_CONDES[ ] = "xxxx";
    constexpr char SAD_CONDES[ ] = "xxxxx"; // essa temp não ta sendo enviada, ignorar ela ou
    adicionar nos envios se necessario

    constexpr char VOLT_R[ ] = "s91424";
    constexpr char VOLT_S[ ] = "xxx";
    constexpr char VOLT_TT[ ] = "xxxx";

    constexpr char CURR_R[ ] = "s91425";
    constexpr char CURR_S[ ] = "xxxx";
    constexpr char CURR_TT[ ] = "xxx";

    constexpr char BAT_INS[ ] = "s91429";
    constexpr char BAT_RET[ ] = "s91430";
    constexpr char BAT_SUC[ ] = "s91431";
    constexpr char BAT_LL[ ] = "s91432";

    constexpr char VIBR_X_SUC[ ] = "s91426";
    constexpr char VIBR_Y_SUC[ ] = "s91427";
    constexpr char VIBR_Z_SUC[ ] = "s91428";

}

// BLE Sensor MAC Addresses
namespace BLEAddresses
{
    constexpr char TEMP_INSU[ ] = "bc: 57: 29: 0e: 25: e5"; //Ble2
    constexpr char TEMP_RET[ ] = "bc: 57: 29: 0e: 2e: b6"; //Ble1
    constexpr char TEMP_SUC[ ] = "bc: 57: 29: 0e: 19: ea"; //Ble4
    constexpr char TEMP_LL[ ] = "bc: 57: 29: 0e: 2f: a3"; //Ble3
    constexpr char TEMP_ENT_CONDES[ ] = "xx: xx: 29: 0e: 19: 7a"; //Ble4
    constexpr char TEMP_SAI_CONDES[ ] = ""; //Ble4
};

```

#endif

Revision #1

Created 9 June 2025 12:25:32 by Patrick Leal

Updated 9 June 2025 12:25:55 by Patrick Leal