

9338

```
#ifndef _ENV_H
#define _ENV_H

#include <stdint.h>

// Definir níveis de log
#define LOG_LEVEL_NONE 0 // Sem logs
#define LOG_LEVEL_ERROR 1 // Apenas erros
#define LOG_LEVEL_WARN 2 // Avisos e erros
#define LOG_LEVEL_INFO 3 // Informações, avisos e erros
#define LOG_LEVEL_DEBUG 4 // Mensagens de debug, informações, avisos e erros

// Definir qual o nível de log ativo
#define CURRENT_LOG_LEVEL LOG_LEVEL_ERROR

// Funções de log condicional com base no nível
#define LOG_LEVEL_ERROR 1
#define LOG_LEVEL_WARN 2
#define LOG_LEVEL_INFO 3
#define LOG_LEVEL_DEBUG 4

// Defina o nível de log atual
#define CURRENT_LOG_LEVEL LOG_LEVEL_DEBUG

// Macros de log condicional com suporte para mensagens simples e formatadas
#if CURRENT_LOG_LEVEL >= LOG_LEVEL_ERROR
#define LOG_ERROR(fmt, ...) \
    do \
    { \
        Serial.printf("[ERROR] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_ERROR(fmt, ...)
#endif
```

```

#if CURRENT_LOG_LEVEL >= LOG_LEVEL_WARN
#define LOG_WARN(fmt, ...) \
    do \
    { \
        Serial.printf("[WARN] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_WARN(fmt, ...)
#endif

#if CURRENT_LOG_LEVEL >= LOG_LEVEL_INFO
#define LOG_INFO(fmt, ...) \
    do \
    { \
        Serial.printf("[INFO] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_INFO(fmt, ...)
#endif

#if CURRENT_LOG_LEVEL >= LOG_LEVEL_DEBUG
#define LOG_DEBUG(fmt, ...) \
    do \
    { \
        Serial.printf("[DEBUG] " fmt "\n", ##__VA_ARGS__); \
        Serial.flush(); \
    } while (0)
#else
#define LOG_DEBUG(fmt, ...)
#endif

// WiFi Network Credentials
constexpr char NETWORK_CLIENT[] = "SmartVac_Telemetria";
constexpr char PASSW[] = "br@skem#2023";

constexpr uint32_t DELAY_MS_READER_TASK = 300; //300ms para que os envios sejam feitos a cada
20s

// Define o atraso em milissegundos para tarefas de leitura (10.000 parece ser um número

```

mágico)

```
// Equipment Identifiers
```

```
namespace Equipment
```

```
{
```

```
    constexpr char TAG[] = "9338";
```

```
    constexpr char TOPIC[] = "v4/matr0575";
```

```
    constexpr char SENDING_SERVER[] = "web.smartvac.app";
```

```
    constexpr uint16_t SENDING_PORT = 1883;
```

```
    constexpr unsigned long SENDING_VELOCITY = 115200;
```

```
    constexpr uint16_t SENDING_KEEPALIVE = 200;
```

```
    constexpr uint32_t DELAY_MS = 500; // Delay time in milliseconds for tasks
```

```
}
```

```
// Voltage Calibration Constants
```

```
struct VoltageCalibration
```

```
{
```

```
    static constexpr float CAL_R = 223.09;
```

```
    static constexpr float CAL_S = 10;
```

```
    static constexpr float CAL_TT = 10;
```

```
};
```

```
// Current Calibration Constants
```

```
struct CurrentCalibration
```

```
{
```

```
    static constexpr int CAL_R = 15.55;
```

```
    static constexpr int CAL_S = 10;
```

```
    static constexpr int CAL_TT = 10;
```

```
};
```

```
// Pin Definitions
```

```
struct Pins
```

```
{
```

```
    static constexpr int CURRENT_R = 34;
```

```
    static constexpr int CURRENT_S = 36;
```

```
    static constexpr int CURRENT_TT = 39;
```

```
    static constexpr int TEMPERATURE = 16;
```

```
    static constexpr int VOLTAGE_R = 35;
```

```
    static constexpr int VOLTAGE_S = 32;
```

```
    static constexpr int VOLTAGE_TT = 33;
```

```
};
```

```

// Sensor Addresses
namespace Sensors
{
    constexpr char INS[] = "s100000365";
    constexpr char RET[] = "s100000366";
    constexpr char SUC[] = "s100000367";
    constexpr char LL[] = "s100000368";
    constexpr char ENT_CONDES[] = "s100000378";
    constexpr char SAD_CONDES[] = "xxxxx"; // essa temp não ta sendo enviada, ignorar ela ou
    adicionar nos envios se necessario

    constexpr char VOLT_R[] = "s100000369";
    constexpr char VOLT_S[] = "xxxx";
    constexpr char VOLT_TT[] = "xxxx";

    constexpr char CURR_R[] = "s100000370";
    constexpr char CURR_S[] = "xxx";
    constexpr char CURR_TT[] = "xxx";

    constexpr char BAT_INS[] = "s100000374";
    constexpr char BAT_RET[] = "s100000375";
    constexpr char BAT_SUC[] = "s100000376";
    constexpr char BAT_LL[] = "s100000377";

    constexpr char VIBR_X_SUC[] = "s100000371";
    constexpr char VIBR_Y_SUC[] = "s100000372";
    constexpr char VIBR_Z_SUC[] = "s100000373";

}

// BLE Sensor MAC Addresses
namespace BLEAddresses
{
    constexpr char TEMP_INSU[] = "bc: 57: 29: 13: ff: 11"; //Ble2
    constexpr char TEMP_RET[] = "bc: 57: 29: 0e: 19: e5"; //Ble1
    constexpr char TEMP_SUC[] = "bc: 57: 29: 0e: 19: 60"; //Ble4
    constexpr char TEMP_LL[] = "bc: 57: 29: 0e: 19: e3"; //Ble3
    constexpr char TEMP_ENT_CONDES[] = "bc: 57: 29: 0e: 26: 1b"; //Ble4
    constexpr char TEMP_SAI_CONDES[] = ""; //Ble4
};

```

#endif

Revision #1

Created 9 June 2025 11:57:27 by Patrick Leal

Updated 9 June 2025 11:57:41 by Patrick Leal